

NATIONAL HEALTH AND AGING TRENDS STUDY (NHATS)

Addendum to Classification of Persons by Dementia Status in the National Health and Aging Trends Study for Follow-up Rounds

October 22, 2015

Revised December 1, 2016

Revised May 13, 2020

Revised June 30, 2021

Revised August 2, 2022

Revised September 23, 2022

Suggested Citation: Kasper, Judith D., Freedman, Vicki A., Spillman, Brenda C., Skehan, Maureen E., and Hu, Mengyao. 2015. Addendum to Classification of Persons by Dementia Status in the National Health and Aging Trends Study for Follow-up Rounds. Baltimore: Johns Hopkins Bloomberg School of Public Health. Available at www.NHATS.org. This technical paper was prepared with funding from the National Institute on Aging (U01AG032947).

This technical paper updates classification of persons by dementia status in the National Health and Aging Trends Study for follow-up rounds. Kasper et al 2013 (Technical Paper #5) describes the types of information that the National Health and Aging Trends Study (NHATS) provides to identify persons with cognitive impairment and our approach to classifying persons as having dementia. Stata and SAS programming statements to create a dementia classification variable in Round 1 are available at the NHATS website (www.nhats.org). This paper describes the information collected and programming statements for creating a dementia classification variable in follow-up rounds of NHATS.

NHATS items for classification of persons with dementia

Three types of information are collected in all rounds of NHATS and can be used to identify persons who are cognitively impaired:

- A report by the sample person or proxy respondent that a doctor told the sample person that he/she had dementia or Alzheimer's disease.
- A score that indicates probable dementia on the AD8 Dementia Screening Interview, which is administered to proxy respondents who are answering the NHATS interview for the sample person. This 8-item instrument assesses memory, temporal orientation, judgment, and function (Galvin et al. 2005, 2006).
- Cognitive tests that evaluate the sample person's memory (immediate and delayed 10-word recall), orientation (date, month, year, and day of the week; naming the President and Vice President), and executive function (clock drawing test). For more details on items and administration see Kasper and Freedman (2015); NHATS Data Collection Procedures (2011).

The information available varies by type of respondent: for self-respondents, report of a diagnosis and cognitive test items; when proxy respondents are used report of a diagnosis, responses to the AD8, and cognitive test results if the proxy said the sample person could be asked these questions.

Details regarding the criteria for dementia classification are in Kasper et al. 2013 (Technical Paper #5) as are results from a sensitivity and specificity analysis against a clinically evaluated sample (Aging, Demographics, and Memory Study (ADAMS) Wave E conducted in 2010; Langa et al. 2005) and comparisons with other population-based estimates of dementia. The criteria and cutpoints developed in Round 1 remain unchanged in subsequent rounds.

Changes to Programming Statements for classification of persons with dementia in follow-up rounds

Because NHATS is a longitudinal study that interviews the same individuals every year, how the information used in the dementia classification variable is collected across rounds changes somewhat across rounds. These changes affect programming statements in the following ways:

- Once a sample person or proxy respondent reports that a doctor told the sample person that he/she had dementia or Alzheimer's disease, this question is not re-asked. Instead it is coded as "previously reported" in all rounds following the round of the initial report.
- The AD8 items, which ask about a change in thinking or a memory problem, are asked of proxy respondents at each round. However, these items are not asked if *in a prior round* a proxy respondent says that the sample person has dementia or Alzheimer's disease in response to any of the AD8 items. A derived variable (cp#dad8dem) has been created in follow-up rounds, which indicates such a response.

Programming statements for follow-up rounds are attached. These take into account the interview changes above.

Updates to Programming Statements

December 1, 2016 (revisions are underlined):

- Round 2: recodes the immediate word recall score for a subset of cases in Round 2 (N=32)
- Round 4: uses cg4todaydat5 instead of cg4todaydat4 when coding the count of correct orientation to date responses

May 13, 2020 (revisions are double underlined):

- Round 5: sets cases with a missing word list in Round 5 to missing on word recall scores and the dementia classification (N=9)

June 30, 2021 (*revisions are in italics*):

- Rounds 4-9: correctly assigns a score of 8 on the AD8 for cases where cp#dad8dem was incorrectly assigned to -1. This correction updates the dementia classification for a small number of cases (N=3 in round 4; 2 in round 5; 1 in rounds 6-9)

August 2, 2022

- The addendum was updated to clarify that these programming statements are for creating a dementia classification variable in rounds 2-9. Programming statements for rounds 10 and 11 are forthcoming.

September 21, 2022

- Rounds 10 and forward: recodes the clock drawing score to align with missing values in previous rounds.

- All rounds (SAS only): Changed the sum function to arithmetic operator + when calculating r#domain65. This change only affects distributions for r#domain65, and does not affect r#demclas.
- Other small updates (fixing typos, assigning formats (SAS only))

References

- Galvin JE, Roe CM, Powlishta KK, Coats MA, Muich SJ, et al. (2005) The AD8: A brief informant interview to detect dementia. *Neurology*, 65(4): 559-564.
- Galvin JE, Roe CM, Xiong C, Morris JC. (2006). Validity and reliability of the AD8 informant interview in dementia. *Neurology*, 67(11): 1942-1948.
- Kasper JD, Freedman VA. 2015. National Health and Aging Trends Study User Guide: Rounds 1, 2, 3 & 4 Final Release. Baltimore: Johns Hopkins University School of Public Health. Available
- Kasper JD, Freedman VA, Spillman BC. 2013. Classification of Persons by Dementia Status in the National Health and Aging Trends Study. Technical Paper #5. Baltimore: Johns Hopkins University School of Public Health. Available at www.NHATS.org. at www.nhats.org.
- Langa KM, Plassman BL, Wallace RB, Herzog AR, Heeringa SG et al. (2005) The Aging, Demographics, and Memory Study: Study Design and Methods. *Neuroepidemiology*, 25:181-191.

SAS Programming Statements for Rounds 2

Subsequent rounds can be programmed by replacing all round 2 variables with the appropriate round.

```
** NOTE: The input file to run this code is the  
NHATS_Round_2_SP_File_v2 **;  
** FORMATS FOR CONSTRUCTED VARIABLES **;  
proc format;  
value demclas  
1="1:Probable dementia"  
2="2:Possible dementia"  
3="3>No dementia"  
-1="-1:Deceased or nursing home resident in R1 and R2"  
-9="-9:Missing"  
;  
value ad8dem  
1="1:Meets dementia criteria"  
2="2:Does not meet dementia criteria"  
;  
value domain_1  
0="0:Does not meet criteria"  
1="1:Meets criteria"  
;  
value domain65_1  
0="0 Not impaired"  
1="Impaired in 1 domain"  
2="Impaired in 2 domains"  
3="Impaired in 3 domains"  
;  
run;  
  
libname nhatsr2 "[location]";  
  
** RUN NHATS_Round_#_Combined_PROC_FORMAT_Statement.sas BEFORE  
CREATING DEMCLAS FOR EACH ROUND**;  
data nhatsr2.Round2;  
set nhatsr2.NHATS_Round_2_SP_File_v2;  
  
** DATE STEP CODE FOR CREATING DEMENTIA CLASSIFICATION VARIABLE **;  
length r2demclas  
r2ad8_dem r2ad8_1-r2ad8_8 r2ad8miss_1-r2ad8miss_8 r2ad8_score  
r2ad8_miss  
r2date_mon r2date_day r2date_yr r2date_dow r2date_sum r2date_sumr  
r2preslast r2presfirst r2vplast r2vpfirst r2presvp r2presvpr  
r2date_prvp  
r2clock_scorer r2irecall r2drecall r2wordrecall0_20  
r2clock65 r2word65 r2datena65 r2domain65  
3;  
label r2demclas="R2 NHATS Dementia Classification";  
if cg2dwrdimmrc = 10 and cg2dwrdlyrc = -3 then cg2dwrdimmrc = -3;  
**USE THIS LINE TO FIX A CODING ERROR IN ROUND 2 ONLY**;
```

```

** 1) SET MISSING (RESIDENTIAL CARE FQ ONLY) AND N.A. (NURSING HOME
RESIDENTS, DECEASED) **;
if r2dresid in (3,5,7) then r2demclas=-9;
if r2dresid in (6,8) then r2demclas=-1;

** 2) CODE PROBABLE IF DEMENTIA DIAGNOSIS REPORTED BY SELF OR PROXY
**;
if hc2disescn9 in (1,7) and is2resptype in (1,2) then r2demclas=1;
** 3a) CODE AD8_SCORE **;
array r2think {*} cp2chgthink1-cp2chgthink8; ** QUESTIONNAIRE ITEMS
**;
array r2ad8item {*} r2ad8_1-r2ad8_8;
array r2ad8miss {*} r2ad8miss_1-r2ad8miss_8;
r2ad8_score =-1;
r2ad8_miss =-1;

do i=1 to dim(r2ad8item);
** INITIALIZE COUNTS TO NOT APPLICABLE**;
r2ad8item{i}=-1;
r2ad8miss{i}=-1;
** ASSIGN VALUES TO AD8 ITEMS IF PROXY AND DEMENTIA CLASS NOT ALREADY
ASSIGNED BY
REPORTED DIAGNOSIS **;
if is2resptype=2 and r2demclas=. then do;
r2ad8item{i}=.;
if r2think{i} in (1,3) then r2ad8item{i}=1; ** PROXY REPORTS A CHANGE
OR ALZ/DEMENTIA **;
else if r2think{i}=2 then r2ad8item{i}=0; ** PROXY REPORTS NO CHANGE
**;
r2ad8_score=sum(of r2ad8item{*}); ** COUNT AD8 ITEMS **;

if r2ad8item{i} in (0,1) then r2ad8miss{i}=0;
else if r2ad8item{i}=. then r2ad8miss{i}=1;
r2ad8_miss=sum(of r2ad8miss{*}); ** COUNT MISSING AD8 ITEMS **;
end;
end;
** 3b) CODE AD8 DEMENTIA CLASS **;
if cp2dad8dem=1 and is2resptype=2 and r2demclas=. then r2ad8_score=8;
**USE THIS LINE FOR ROUNDS 4-9 ONLY**;
if is#resptype=2 and cp#dad8dem=-1 and cp#chgthink1=-1 then
r#ad8_score=8;

if r2ad8_score>=2 then r2ad8_dem=1 ; ** IF SCORE >=2 THEN MEETS AD8
CRITERION **;
if (r2ad8_score in (0,1) or r2ad8_miss=8) and r2ad8_dem=. then
r2ad8_dem=2; ** IF SCORE IS 0 OR 1 OR ALL ITEMS MISSING THEN DOES NOT
MEET AD8 CRITERION **;
** 4) UPDATE DEMENTIA CLASSIFICATION VARIABLE WITH AD8 CLASS **;
if r2demclas=. then do;
if r2ad8_dem=1 then r2demclas=1; ** PROBABLE BASED ON AD8 SCORE **;
if r2ad8_dem=2 and cg2speaktosp=2 then r2demclas=3; ** NO DIAGNOSIS,
DOES NOT MEET AD8

```

```

CRITERION, AND PROXY SAYS CANNOT ASK SP COGNITIVE ITEMS **;
end;
** 5) CODE DATE ITEMS AND COUNT **;
array cg2date {*} cg2todaydat1-cg2todaydat4; **USE THIS LINE FOR
ROUNDS 1-3, 5 and forward**;
array cg4date {*} cg4todaydat1 cg4todaydat2 cg4todaydat3 cg4todaydat5;
**USE THIS LINE FOR ROUND 4**;
array r2date_item {*} r2date_mon r2date_day r2date_yr r2date_dow;

do i=1 to dim(r2date_item);
  if cg2date{i} > 0 then r2date_item{i}=cg2date{i}; *** CODE ONLY
YES/NO RESPONSES: MISSING/N.A.
CODES -1,-9 LEFT MISSING **;
  if cg2date{i} in (-7,2) then r2date_item{i}=0; ** 2:NO/DK OR -
7:REFUSED RECODED TO 0:NO/DK/RF
**;
  r2date_sum=sum(of r2date_item{*}); ** COUNT CORRECT DATE ITEMS
**;
end;
if r2date_sum=. then do;
  if cg2speaktosp=2 then r2date_sum=-2; ** PROXY SAYS CAN'T SPEAK TO SP
**;
  else if cg2speaktosp=1 and max(of cg2date{*})=-1 then r2date_sum=-3;
** PROXY SAYS CAN SPEAK TO
SP BUT SP UNABLE TO ANSWER **;
end;
r2date_sumr=r2date_sum;
if r2date_sum=-2 then r2date_sumr=.; ** MISSING IF PROXY SAYS CAN'T
SPEAK TO SP
**;
else if r2date_sum=-3 then r2date_sumr=0; ** 0 IF SP UNABLE TO ANSWER
**;
** 6) PRESIDENT AND VICE PRESIDENT NAME ITEMS AND COUNT **;
array cg2pres {*} cg2presidna1 cg2presidna3 cg2vpname1 cg2vpname3;
array r2pres_item {*} r2preslast r2presfirst r2vplast r2vpfirst;
do i=1 to dim(r2pres_item);
  if cg2pres{i} > 0 then r2pres_item{i}=cg2pres{i}; ** CODE ONLY YES/NO
RESPONSES: MISSING/N.A. CODES
-1,-9 LEFT MISSING **;
  if cg2pres{i} in (-7,2) then r2pres_item{i}=0; ** 2:NO/DK OR -
7:REFUSED RECODED TO 0:NO/DK/RF
**;
  r2presvp=sum(of r2pres_item{*}); ** COUNT CORRECT PRESIDENT/VEEP NAME
ITEMS
**;
end;
if r2presvp=. then do;
  if cg2speaktosp=2 then r2presvp=-2; ** PROXY SAYS CAN'T SPEAK TO SP
**;
  else if cg2speaktosp=1 and max(of cg2pres{*})=-1 then r2presvp=-3; **
PROXY SAYS CAN SPEAK TO SP

```

```

BUT SP UNABLE TO ANSWER **;
end;
r2presvpr=r2presvp;
if r2presvp=-2 then r2presvpr=.; ** MISSING IF PROXY SAYS CAN'T SPEAK
TO SP **;
else if r2presvp=-3 then r2presvpr=0; ** 0 IF SP UNABLE TO ANSWER **;
** 7) ORIENTATION DOMAIN: SUM OF DATE RECALL AND PRESIDENT NAMING **;
r2date_prvp=sum(r2date_sumr,r2presvpr);
** 8) EXECUTIVE FUNCTION DOMAIN: CLOCK DRAWING SCORE **;
*RECODE CLOCK DRAWING SCORE TO ALIGN WITH MISSING VALUES IN PREVIOUS
ROUNDS (ROUND 10 ONLY)*;
if cg#speaktosp=2 and cg#dclkdraw=-9 then cg#dclkdraw=-2;
if cg#speaktosp=1 and cg#quesremem in (2, -7, -8) and cg#dclkdraw=-9
then cg#dclkdraw=-3;
if cg#atdrwclck=2 and cg#dclkdraw=-9 then cg#dclkdraw=-4;
if cg#atdrwclck=97 and cg#dclkdraw=-9 then cg#dclkdraw=-7;
*RECODE CLOCK DRAWING SCORE TO ALIGN WITH MISSING VALUES IN PREVIOUS
ROUNDS (ROUNDS 11 AND FORWARD ONLY)*;
if cg#speaktosp=2 and cg#dclkdraw=-9 then cg#dclkdraw=-2;
if cg#speaktosp=1 and cg#quesremem in (2, -7, -8) and cg#dclkdraw=-9
then cg#dclkdraw=-3;

r2clock_scorer=cg2dclkdraw;
if cg2dclkdraw in (-2,-9) then r2clock_scorer=.;
if cg2dclkdraw in (-3,-4,-7) then r2clock_scorer=0;
** IMPUTE MEAN SCORE TO PERSONS MISSING A CLOCK **;
if cg2dclkdraw=-9 and cg2speaktosp=1 then r2clock_scorer=2; ** IF
PROXY SAID CAN ASK SP **;
if cg2dclkdraw=-9 and cg2speaktosp=-1 then r2clock_scorer=3; ** IF
SELF RESPONDENT **;
** 9) MEMORY DOMAIN: IMMEDIATE AND DELAYED WORD RECALL **;
array cg2recall {*} cg2dwrdimmrc cg2dwrdlyrc;
array r2word_recall {*} r2irecall r2drecall;
do i=1 to dim(r2word_recall);
  r2word_recall{i}=cg2recall{i};
  if cg2recall{i} in (-2,-1) then r2word_recall{i}=.;
  if cg2recall{i} in (-7,-3) then r2word_recall{i}=0;
**SET CASES WITH MISSING WORD LIST AND NOT PREVIOUSLY ASSIGNED TO
MISSING (ROUND 5 ONLY)**;
if cg5dwrdimmrc=-9 then r5word_recall{i}=.;
r2wordrecall0_20=sum(of r2word_recall{*});
end;
** 10) CREATE COGNITIVE DOMAINS FOR ALL ELIGIBLE **;
** I.E. PROXY BUT PROXY SAYS CAN ASK SP, NOT FQ ONLY, NOT NH **;
if 1 < r2clock_scorer <=5 then r2clock65=0;
if 0 <= r2clock_scorer <=1 then r2clock65=1;
if 3 < r2wordrecall0_20 <=20 then r2word65=0;
if 0 <= r2wordrecall0_20 <=3 then r2word65=1;
if 3 < r2date_prvp <= 8 then r2datena65=0;
if 0 <= r2date_prvp <= 3 then r2datena65=1;
** 10) CREATE COGNITIVE DOMAIN SCORE **;
array r2domains {*} r2clock65 r2word65 r2datena65;

```

```
do i=1 to dim(r2domains);
  r2domain65= r2clock65 + r2word65 + r2datena65;
end;
**SET CASES WITH MISSING WORD LIST AND NOT PREVIOUSLY ASSIGNED TO
MISSING (ROUND 5 ONLY)**;
if cg5dwrdlstnm=-9 and r5demclas=. then r5demclas=-9;
** 11) UPDATE COGNITIVE CLASSIFICATION **;
if r2demclas=. and cg2speaktosp in (-1,1) then do;
  if 2 <= r2domain65 <=3 then r2demclas=1; ** PROBABLE DEMENTIA **;
  if r2domain65 =1 then r2demclas=2; ** POSSIBLE DEMENTIA **;
  if r2domain65 =0 then r2demclas=3; ** NO DEMENTIA **;
end;

format
r2demclas demclas.
r2ad8_dem ad8dem.
r2clock65 r2word65 r2datena65 domain_1.
r2domain65 domain65_1.;

run;
```

Stata programming statements for Round 2

Subsequent rounds can be programmed by replacing all round 2 variables with the appropriate round.

```
** NOTE: The input file to run this code is the NHATS_Round_2_SP_File**
*USE THIS LINE TO FIX A CODING ERROR IN ROUND 2 ONLY
replace cg2dwrdimmrc=-3 if cg2dwrdimmrc==10 & cg2dwrrdlyrc==3
*SET MISSING (RESIDENTIAL CARE FQ ONLY) AND N.A. (NURSING HOME RESIDENTS, DECEASED)*
gen r2demclas=-9 if r2dresid==3 | r2dresid==5 | r2dresid==7
replace r2demclas=-1 if r2dresid==6 | r2dresid==8
*CODE PROBABLE IF DEMENTIA DIAGNOSIS REPORTED BY SELF OR PROXY*
replace r2demclas=1 if (hc2disescn9==1 | hc2disescn9==7) & (is2resptype==1 | is2resptype==2)
tab r2demclas
*CODE AD8_SCORE*
*INITIALIZE COUNTS TO NOT APPLICABLE*
*ASSIGN VALUES TO AD8 ITEMS IF PROXY AND DEMENTIA CLASS NOT ALREADY ASSIGNED BY REPORTED
DIAGNOSIS
foreach num of numlist 1/8 {
    *INITIALIZE COUNTS TO NOT APPLICABLE*
    gen r2ad8_`num'=-1
    replace r2ad8_`num'=. if is2resptype==2 & r2demclas==.
    *PROXY REPORTS A CHANGE OR ALZ/DEMENTIA*
    replace r2ad8_`num'=1 if is2resptype==2 & r2demclas==. & (cp2chgthink`num'==1 |
    cp2chgthink`num'==3)
    *PROXY REPORTS NO CHANGE*
    replace r2ad8_`num'=0 if is2resptype==2 & r2demclas==. & (cp2chgthink`num'==2) & r2ad8_`num'==.
}

foreach num of numlist 1/8 {
    *INITIALIZE COUNTS TO NOT APPLICABLE*
    gen r2ad8miss_`num'=-1
    replace r2ad8miss_`num'=0 if is2resptype==2 & r2demclas==. & (r2ad8_`num'==0 |
    r2ad8_`num'==1)
    replace r2ad8miss_`num'=1 if is2resptype==2 & r2demclas==. & r2ad8_`num'==.
    replace r2ad8_`num'=0 if is2resptype==2 & r2demclas==. & r2ad8_`num'==.
}

*COUNT AD8 ITEMS*
gen r2ad8_score=-1
replace r2ad8_score=(r2ad8_1+r2ad8_2+r2ad8_3+r2ad8_4+r2ad8_5+r2ad8_6+r2ad8_7+r2ad8_8) if
is2resptype==2 & r2demclas==.
*SET PREVIOUS ROUND DEMENTIA DIAGNOSIS BASED ON AD8 TO AD8_SCORE=8*
replace r2ad8_score=8 if cp2dad8dem==1 & is2resptype==2 & r2demclas==.
*USE THIS LINE FOR ROUNDS 4-9 ONLY*
replace r#ad8_score=8 if is#resptype==2 & cp#dad8dem==1 & cp#chgthink1==1

*COUNT MISSING AD8 ITEMS*
gen r2ad8_miss= -1
```

```

replace
r2ad8_miss=(r2ad8miss_1+r2ad8miss_2+r2ad8miss_3+r2ad8miss_4+r2ad8miss_5+r2ad8miss_6+r2ad8
miss_7+r2ad8miss_8) if is2resptype==2 & r2demclas==.

*CODE AD8 DEMENTIA CLASS*
*IF SCORE>=2 THEN MEETS AD8 CRITERIA*
gen r2ad8_dem=1 if r2ad8_score>=2
* IF SCORE IS 0 OR 1 OR ALL ITEMS MISSING THEN DOES NOT MEET AD8 CRITERION*
replace r2ad8_dem=2 if (r2ad8_score==0 | r2ad8_score==1 | r2ad8_miss==8) & r2ad8_dem==.

*UPDATE DEMENTIA CLASSIFICATION VARIABLE WITH AD8 CLASS*
*PROBABLE DEMENTIA BASED ON AD8 SCORE*
replace r2demclas=1 if r2ad8_dem==1 & r2demclas==.
*NO DIAGNOSIS, DOES NOT MEET AD8 CRITERION, AND PROXY SAYS CANNOT ASK SP COGNITIVE
ITEMS*
replace r2demclas=3 if r2ad8_dem==2 & cg2speaktosp==2 & r2demclas==.
tab r2demclas

*CODE DATE ITEMS AND COUNT*
*USE THE FOLLOWING LOOP FOR ROUNDS 1-3, 5, and forward*
foreach num of numlist 1/4 {
    *CODE ONLY YES/NO RESPONSES: MISSING/NA CODES -1, -9 LEFT MISSING*
    gen r2date_item`num'=cg2todaydat`num' if cg2todaydat`num'>0
    *2: NO/DK OR -7: REFUSED RECODED TO : NO/DK/RF*
    replace r2date_item`num'=0 if cg2todaydat`num'==2 | cg2todaydat`num'==-7
}

*USE THE FOLLOWING LOOP FOR ROUND 4*
foreach num of numlist 1/5 {
    *CODE ONLY YES/NO RESPONSES: MISSING/NA CODES -1, -9 LEFT MISSING*
    gen r4date_item`num'=cg4todaydat`num' if cg4todaydat`num'>0
    *2: NO/DK OR -7: REFUSED RECODED TO : NO/DK/RF*
    replace r4date_item`num'=0 if cg4todaydat`num'==2 | cg4todaydat`num'==-7
}

*COUNT CORRECT DATE ITEMS*
gen r2date_sum=r2date_item1 + r2date_item2 + r2date_item3 + r2date_item4 //USE THIS LINE FOR
ROUNDS 1-3, 5 and forward

gen r4date_sum=r4date_item1 + r4date_item2 + r4date_item3 + r4date_item5 //USE THIS LINE FOR
ROUND 4

*PROXY SAYS CAN'T SPEAK TO SP*
replace r2date_sum=-2 if r2date_sum==. & cg2speaktosp==2
*PROXY SAYS CAN SPEAK TO SP BUT SP UNABLE TO ANSWER*
replace r2date_sum=-3 if (r2date_item1==. | r2date_item2==. | r2date_item3==. | r2date_item4==.) &
cg2speaktosp==1

gen r2date_sumr=r2date_sum

```

MISSING IF PROXY SAYS CAN'T SPEAK TO SP

replace r2date_sumr=. if r2date_sum==2

0 IF SP UNABLE TO ANSWER

replace r2date_sumr=0 if r2date_sum==3

PRESIDENT AND VICE PRESIDENT NAME ITEMS AND COUNT

** CODE ONLY YES/NO RESPONSES: MISSING/N.A. CODES -1,-9 LEFT MISSING *

2:NO/DK OR -7: REFUSED RECODED TO 0:NO/DK/RF

gen r2preslast=cg2presidna1 if cg2presidna1>0

replace r2preslast=0 if cg2presidna1==7 | cg2presidna1==2

gen r2presfirst=cg2presidna3 if cg2presidna3>0

replace r2presfirst=0 if cg2presidna3==7 | cg2presidna3==2

gen r2vpplast=cg2vpname1 if cg2vpname1>0

replace r2vpplast=0 if cg2vpname1==7 | cg2vpname1==2

gen r2vpfirst=cg2vpname3 if cg2vpname3>0

replace r2vpfirst=0 if cg2vpname3==7 | cg2vpname3==2

COUNT CORRECT PRESIDENT/VP NAME ITEMS

gen r2presvp= r2preslast+r2presfirst+r2vpplast+r2vpfirst

** PROXY SAYS CAN'T SPEAK TO SP *

replace r2presvp=-2 if r2presvp==. & cg2speaktosp==2

** PROXY SAYS CAN SPEAK TO SP BUT SP UNABLE TO ANSWER *

replace r2presvp=-3 if r2presvp==. & cg2speaktosp==1 & (r2preslast==. | r2presfirst==. | r2vpplast==. | r2vpfirst==.)

gen r2presvpr=r2presvp

MISSING IF PROXY SAYS CAN'T SPEAK TO SP

replace r2presvpr=. if r2presvp==2

0 IF SP UNABLE TO ANSWER

replace r2presvpr=0 if r2presvp==3

ORIENTATION DOMAIN: SUM OF DATE RECALL AND PRESIDENT/VP NAMING

gen r2date_prvp=r2date_sumr + r2presvpr

EXECUTIVE FUNCTION DOMAIN: CLOCK DRAWING SCORE

RECODE CG#DCLKDRAW TO ALIGN WITH MISSING VALUES IN PREVIOUS ROUNDS (ROUND 10 ONLY)

replace cg#dclkdraw=-2 if cg#speaktosp==2 & cg#dclkdraw==9

replace cg#dclkdraw=-3 if cg#speaktosp==1 & (cg#quesremem==2 | cg#quesremem==7 | cg#quesremem==8) & cg#dclkdraw==9

replace cg#dclkdraw=-4 if cg#atdrwclck==2 & cg#dclkdraw==9

replace cg#dclkdraw=-7 if cg#atdrwclck==97 & cg#dclkdraw==9

RECODE CG#DCLKDRAW TO ALIGN WITH MISSING VALUES IN PREVIOUS ROUNDS (ROUNDS 11 AND FORWARD ONLY)

replace cg#dclkdraw=-2 if cg#speaktosp==2 & cg#dclkdraw==9

replace cg#dclkdraw=-3 if cg#speaktosp==1 & (cg#quesremem==2 | cg#quesremem==7 | cg#quesremem==8) & cg#dclkdraw==9

```

gen r2clock_scorer=cg2dclkdraw
replace r2clock_scorer=. if cg2dclkdraw== -2 | cg2dclkdraw== -9
replace r2clock_scorer=0 if cg2dclkdraw== -3 | cg2dclkdraw== -4 | cg2dclkdraw== -7
*IMPUTE MEAN SCORE TO PERSONS MISSING A CLOCK*
*IF PROXY SAID CAN ASK SP*
replace r2clock_scorer=2 if cg2dclkdraw== -9 & cg2speaktosp==1
*IF SELF-RESPONDENT*
replace r2clock_scorer=3 if cg2dclkdraw== -9 & cg2speaktosp== -1

*MEMORY DOMAIN: IMMEDIATE AND DELAYED WORD RECALL*
gen r2irecall=cg2dwrddimmrc
replace r2irecall=. if cg2dwrddimmrc== -2 | cg2dwrddimmrc== -1
replace r2irecall=0 if cg2dwrddimmrc== -7 | cg2dwrddimmrc== -3
*SET CASES WITH MISSING WORD LIST AND NOT PREVIOUSLY ASSIGNED TO MISSING (ROUND 5 ONLY)
replace r5irecall=. if cg5dwrddimmrc== -9

gen r2drecall=cg2dwrddlyrc
replace r2drecall=. if cg2dwrddlyrc== -2 | cg2dwrddlyrc== -1
replace r2drecall=0 if cg2dwrddlyrc== -7 | cg2dwrddlyrc== -3
*SET CASES WITH MISSING WORD LIST AND NOT PREVIOUSLY ASSIGNED TO MISSING (ROUND 5 ONLY)
replace r5drecall=. if cg5dwrddlyrc== -9

gen r2wordrecall0_20=r2irecall+r2drecall

*CREATE COGNITIVE DOMAINS FOR ALL ELIGIBLE*
gen r2clock65=0 if r2clock_scorer>1 & r2clock_scorer<=5
replace r2clock65=1 if r2clock_scorer>=0 & r2clock_scorer<=1

gen r2word65=0 if r2wordrecall0_20>3 & r2wordrecall0_20<=20
replace r2word65=1 if r2wordrecall0_20>=0 & r2wordrecall0_20<=3

gen r2datena65=0 if r2date_prvp>3 & r2date_prvp<=8
replace r2datena65=1 if r2date_prvp>=0 & r2date_prvp<=3

*CREATE COGNITIVE DOMAIN SCORE*
gen r2domain65 = r2clock65+r2word65+r2datena65

*SET CASES WITH MISSING WORD LIST AND NOT PREVIOUSLY ASSIGNED TO MISSING (ROUND 5 ONLY)
replace r5demclas=-9 if cg5dwrldstnm== -9 & r5demclas== -

*UPDATE COGNITIVE CLASSIFICATION*
*PROBABLE DEMENTIA*
replace r2demclas=1 if r2demclas==. & (cg2speaktosp==1 | cg2speaktosp== -1) & (r2domain65==2 | r2domain65==3)
*POSSIBLE DEMENTIA*
replace r2demclas=2 if r2demclas==. & (cg2speaktosp==1 | cg2speaktosp== -1) & r2domain65==1
*NO DEMENTIA*

```

```
replace r2demclas=3 if r2demclas==. & (cg2speaktosp==1 | cg2speaktosp==-1) & r2domain65==0

*Label variables and values*
label variable r2ad8_dem "Dementia classification based on proxy AD8 report"
label define r2ad8_dem_values 1 "1 Meets dementia criteria" 2 "2 Does not meet dementia criteria"
label values r2ad8_dem r2ad8_dem_values
label variable r2demclas "R2 NHATS Dementia Classification"
label define dementialabel652 1 "1 Probable dementia" 2 "2 Possible dementia" 3 "3 No dementia" -1 "-1 Deceased or nursing home resident in R1 and R2" -9 "-9 Missing"
label values r2demclas dementialabel652
label define domain_labels2 0 "0 Does not meet criteria" 1 "1 Meets criteria"
label values r2clock65 r2word65 r2datena65 domain_labels2
label define domain65_label2 0 "0 Not impaired" 1 "Impaired in 1 domain" 2 "Impaired in 2 domains" 3 "Impaired in 3 domains"
label values r2domain65 domain65_label2
tab r2demclas
```